



CEROIL DPF CLEANER KIT 2 PHASES

Particulate filter cleaner (DPF/FAP)

Ceroil DPF Cleaner Kit 2 Phases is a high performance cleaner that regenerates and removes soot from the DPF/FAP quickly and safely, reducing maintenance costs.

Due to the stop & go driving that is done on short journeys, the DPF/FAP does not reach the temperature to remove the soot that is deposited on it. Engines automatically regenerate the DPF by injecting diesel to cause combustion in the DPF, but this type of driving prevents the process and soot accumulates excessively. This causes the DPF warning light to come on and a loss of engine power, as well as excessive fuel consumption and possible breakdowns.

<u>If used in vehicles equipped with ADBLUE SCR system</u> <u>previously remove the ADBLUE sensor.</u>

PHASE 1 - DECARBONISING

It is a degreasing and decarbonizing active ingredient based on polyalcohol solvents and anticorrosive inhibitors, especially for removing persistent grease and carbon (contains NaOH). Due to its great cleaning power, it removes carbon and more stubborn dirt without the need for disassembly, mechanical efforts or aggressive products.

UTILITY

In cases of clogged filter or failure signal. To return to the filter its regenerative capacity. As a preventive in cases of short driving or Stop & Go.

CHARACTERISTICS

Thanks to the chemical formulas and the application method provided by the kit, a deep action is achieved on the honeycomb filter element mounted inside the particulate filters.

The products that make up the kit easily eliminate carbonaceous residues and soot that clog the normal passage of exhaust gases from the engine, facilitating the forced regeneration operation. Very quick operation to perform without the need for disassembly.

Products specifically designed not to ruin the noble metals present in the filters. Very cheap repair.

ADVANTAGES

- Cleans and regenerates the DPF/FAP diesel particulate filter.
- Reduces the combustion temperature of soot in the DPF/FAP.
- Extends the life of the particulate filter.
- Ideal treatment for vehicles that make short journeys.



CEROIL PRODUCT, S.L. – Calle Mestral s/n; Recinto SERTRANS; Pol. Ind. Can Volart – 08150 – Parets del Vallès – Barcelona - Tel. +34 93.160.05.30 – www.ceroil.com – info@ceroil.com

TECHNICAL DATA SHEET



CEROIL DPF CLEANER KIT 2 PHASES

Particulate filter cleaner (DPF/FAP)

APPLICATION

- 1. Fill the gun with the Decarbonizer (Phase 1)
- 2. Raise the engine temperature to its normal level and shut off the engine.
- 3. Insert the pistol (or the blue cannula) through the hole of the Lambda probe or the temperature sensor.
- 4. The gun must be at a pressure of 5-6 bars.
- 5. Apply the product to the filter in the direction of the gas outlet for 15 seconds and repeat the operation until the product is used up. Then wait 10 minutes.
- 6. Start the engine for 2 to 3 minutes accelerating to 2,000-3,000 rpm.
- 7. Foam may be coming out of the exhaust pipe.





ASPECT:	Liquid
COLOUR:	Transparent
ODOR:	Alcoholic
DENSITY:	1,05 gr./cc 200°C
pH 10%:	13
FLASH POINT:	Non flammable



CEROIL PRODUCT, S.L. – Calle Mestral s/n; Recinto SERTRANS; Pol. Ind. Can Volart – 08150 – Parets del Vallès – Barcelona - Tel. +34 93.160.05.30 – www.ceroil.com – info@ceroil.com

TECHNICAL DATA SHEET



CEROIL DPF CLEANER KIT 2 PHASES

Particulate filter cleaner (DPF/FAP)

PHASE 2 - NEUTRALIZER

Circuit neutralizing acid product for cleaning DPF particulate filters. Essential for cleaning particulate filters, in which Ceroil Phase 1 Descaler is previously used.

ADVANTAGES

- Neutralizes the active substance of the Descaling Cleaner (Phase 1)
- Allows a complete rinsing of the DPF.
- Remove any carbon particles that may remain from the initial cleaning.

APPLICATION

- 1. Rinse the gun with plenty of water to remove the remains of the Decarbonizer (Phase 1)
- 2. Fill the gun with the Neutralizer (Phase 2).
- 3. With the engine off, spray the entire product through the Banda Lambda probe or the temperature sensor, spraying at 15-second intervals.
- 4. Foam may come out of the exhaust pipe.
- 5. Force the start of the DPF regeneration cycle by driving 30 to 40 km with a high and constant engine revolution level (3,000 to 4,000 rpm) or electronically through the control unit.

CHARACTERISTICS

ASPECT:	Transparent Liquid
COLOUR:	Pinkish
DENSITY 20°c:	1.27 gr/cc +/- 0.05
рН 1%:	1-2



TECHNICAL DATA SHEET



CEROIL DPF CLEANER KIT 2 PHASES

Particulate filter cleaner (DPF/FAP)

THE KIT CONSIST OF:

- DESCARBONISING
- NEUTRALIZER

Reference	Capacity
CO0050HNA	1L + 1L
CO0050JNA	5L + 5L



CEROIL PRODUCT, S.L. – Calle Mestral s/n; Recinto SERTRANS; Pol. Ind. Can Volart – 08150 – Parets del Vallès – Barcelona - Tel. +34 93.160.05.30 – www.ceroil.com – info@ceroil.com