

CEROIL ENGINE CLEANER

Cleaning additive for the engine oil

PRODUCT

Cleaning additive for the engine oil. Removes all types of waste, sediments and scale from inside the crankcase. Aluminum bottle.

UTILITY

It can be used in gasoline and diesel engines. Applicable to all internal engine parts: sump, connecting rods, crankshaft, camshaft, valves, segments, oil pump, lodgings, hydraulic systems, replacement boxes, bolts, etc.

ADVANTAGES

- Removes all types of residus sediments and crankcase fouling.
- Extends services and improves the circulation of new oil.
- Is not corrosive. Does not affect the rubbers plastics and metals.
- Miscible with all mineral and synthetic oil.

APPLICATION

- 1- Start the engine until it reaches the working temperature.
- 2- Pour the contents of the container into the engine oil.
- 3- Let the engine slow motion for 10-15 min.
- 4- Stop the engine and empty completely the oil sump.
- 5- Put new engine oil and change the filter as well.



Reference	Capacity	Box Units
C00029FNA	500 ml.	12
C00029HNA	1 L.	12
C00029JNA	5 L.	4
C00029KNA	25 L.	-

TECHNICAL DATA	
Appearance	Transparent liquid
Color	Pardo
Density a 20°C	1,010 – 1.040 g / cc
Tª inflammation	60°C

DOSE

The right proportion of use is 0,5 liters each 4-6 liters of oil.



Respectful with ENVIRONMENT