

CEROIL REFRIGERANT – ANTIFREEZE C.C.10%

Organic refrigerant antifreeze

Version 1 Date of issue: 01/03/2023

Page 1 de 1 Date of Printing: 26/05/2023

PRODUCT

New generation coolant-antifreeze manufactured with 10% glycols, with corrosion inhibitors and distilled-demineralized water. For all types of vehicles. Direct use.

PROPERTIES

Does not contain nitrites or amines. Prevents the formation of decompositions harmful to vehicles and people. Excellent thermal conductivity. It begins to crystallize in the laboratory at -3.5°C. It meets all the specifications required worldwide for this type of products and therefore its use is guaranteed for any vehicle, machinery, etc. Does not produce foaming





Available in 1L. and 5L.

TECHNICAL DATA

| ANTIFREEZE- COOLANTC.C.10% | Méthod | Value |
|--------------------------------|-------------|-------------|
| Aspect | Visual | Liquid |
| Coloi f | Visual | MY``ck |
| Densihma 20°C, kg/l | ASTM D-4052 | 1.013-1.023 |
| RYZfaVMjcn'InXYI, °C | ASTM D-1218 | 1.340-1.345 |
| A`_a`]nY`RYgYfj Y, ml HCl 0.1N | ASTM D-1121 | 1.0-3.0 |
| FfYYn]n[dc]nh, °C | ASTM D-1177 | -4°C+/-1% |
| pH | ASTM D-1287 | 7.5-9.0 |

Quality levels/ UNE Specifications 26.361.88

